


## MC 746

**DISCONTINUED** - Replaced by MC 746-EMagnetic Contact  
Surface mount, NC/NO**Technical data**

Installation method	Surface mount
Contact function	Change-over (NC/NO)
Contact rating	48 VDC / 250 mA / 5 VA
Magnet type	Alnico 5
Mounting on steel	Not recommended
Make distance (wood) mm	37
Make distance (steel) mm	X
Tamper protection	Yes
Connection	Cable
Housing material	ABS Plastic
Operating temperature range	-40°C - +70°C
Housing protection class	IP 67
Contact dimensions (L x W x H) mm	60 x 14 x 5
Magnet dimensions (L x W x H) mm	60 x 14 x 5
Grade	2



MC 746 is a small and thin magnetic contact with change-over (NC/NO) function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing. The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.

**ORDERING INFORMATION**

Model	Description
MC 746	Magnetic contact, NC, surface mount, 2 m cable
MC 746-6	Magnetic contact, NC, surface mount, 6 m cable
MC 746-10	Magnetic contact, NC, surface mount, 10 m cable