


MC 740P BL

DISCONTINUED - Replaced by MC 740-PEMagnetic Contact
Surface mount, NC**Technical data**

Installation method	Surface mount
Contact function	Normally Closed (NC)
Approvals	EN 50131-2-6 Grade 2, Class IIIA, INCERT B-582-0013, VdS G 116504, Class B, SBSC 9-216, Class 1/2, F&P, FG
Contact rating	48 VDC / 500 mA / 10 VA
Magnet type	Alnico 5
Mounting on steel	Not recommended
Make distance (wood) mm	37
Make distance (steel) mm	7
Connection	Cable
Housing material	ABS Plastic
Colour	Black
Operating temperature range	-40°C - +70°C
Housing protection class	IP 67
Contact dimensions (L x W x H) mm	58 x 14 x 5
Magnet dimensions (L x W x H) mm	58 x 14 x 5



MC 740 is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing.

The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.

ORDERING INFORMATION

Code	Description
MC 740P-2BL	Magnetic contact, black, surface mount NC, 2 m cable
MC 740P-6BL	Magnetic contact, black, surface mount NC, 6 m cable