

# PSV 2465-A1

## Power supply unit, ViP, 24 VDC 6.5 A



### Technical data

Approvals	EN-ST-000216/Grade 3, EN 50131-6 Grade 3, EN 50130-5 Class II, Safety EN 62368-1, EMC EN 61000-6-3, SE-100168, 21-205 Class 3, FG 10.212-14801, F&P E-1030/21
Supply voltage	230 VAC
Output voltage	27,6 VDC
Output current	6,5 A
Space for accumulator (not included)	2x 12 V/40 Ah
Tamper protection	Opening and pry off switches, max 48V / 100 mA
Housing material	Metal
Colour	Grey
Dimensions (L x W x H) mm	425 x 440 x 200
Grade	3



Power supply unit with battery charging and ViP (Voltage in Parallel) function, 24 VDC 6.5 A.

Power supply unit with ViP function can be connected in parallel to provide more power and redundancy and compensate for voltage drop in the cables. Each battery backup can be installed as a standalone unit or to be connected via plus and minus with one or more power supply units. By connecting several units to each other, you can get more current and compensate for voltage drops in the wiring and thus achieve higher redundancy in the system.

Space is provided for two 12V/40Ah accumulator in the metal box which also has opening and pry-off switches. The unit is protected against short-circuiting and overload. Mains failure, low output voltage, battery and fuse failure is indicated via LED and activates separate outputs with relays.

### ORDERING INFORMATION

Model	Description
PSV 2465-A1	Power supply unit with battery charging and ViP function, 24 V 6,5 A, Grey