

## MC 140

## Magnetic Contact, Recessed mounting, NC



## Technical data

|                               |  |
|-------------------------------|--|
| Installation method           | Recessed mounting  |
| Contact function              | Normally Closed (NC)   |
| Approvals                     | SBSC 10-30, Class 2; INCERT B-582-1003, EN-ST-000094 Grade 2, class II |
| Contact rating                | 48 VDC / 400 mA / 10 VA  |
| Drill diameter mm             | 19-20  |
| Magnet type                   | Neodymium (NdFeB)  |
| Make distance (wood) mm       | 21   |
| Make distance (steel) mm      | X  |
| Tamper protection             | Yes  |
| Connection                    | Screw terminals  |
| Housing material              | ABS Plastic  |
| Operating temperature range   | -40 - +70 °C   |
| Housing protection class      | IP 43  |
| Contact dimensions (L x Ø) mm | 19 x 35  |
| Magnet dimensions (L x Ø) mm  | 12 x 35  |
| Operating temperature         | -40 - +70 °C   |
| Grade                         | 2  |



MC 140 is a magnetic contact with NC function that can be used both in alarm and access control systems for recessed installation in doors and windows. Its small size and screw terminal connection makes it easy to install in most locations.

MC 140 is not suitable for installation in steel frames.

