

# GD 330

## Glass Break Detector, Glued



### Product :

Zone de couverture max.	2 m radio (standard 3 mm glass)
Certifications	EN 50131-2-7-2:2013 Grade 2, VdS class B - G192531, SBSC 10-31 Klasse 2
Tension de l'alimentation	8-15 VDC
Consommation électrique	5 mA (12 mA alarm)
Cote commutateur	50 VDC / 100 mA
Indicateur d'alarme	LED
Autoprotection	Oui
Durée alarme	Latching
Réinitialisation alarme	Power down
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	ABS Plastic
Couleur	Blanc
Température de fonctionnement	-40°C - +70°C
Indice de protection	IP 67
Dimensions (h x Ø) mm	16 x 35
Grade	2








### Product description:

The GD 330 is a glass break detector with relay output that can be directly connected to a control panel. It is especially designed for monitoring shop windows, sliding glass doors, ordinary windows and other exposed glass surfaces, both in public spaces and private homes. It can be used on windows with protective film if the detector is mounted directly onto the glass and not on the film (a 5-10 cm hole must be cut out the film). It can also be used on glass cabinets to protect various types of equipment. The GD 330 glass break detector is activated when the glass is shattered or broken and is highly resistant to interference with the glass or in its immediate environment, which makes it ideal for 24-hour monitoring. Its circular design guarantees correct positioning. The GD 330 is glued to the glass pane and each detector is supplied with a stencil to mark the mounting location, a glue applicator and cable clamps for quick and easy installation.

**For laminated and tempered glass please use GD 370 or GD 470.**

**Related products and accessories**

 The image shows a white plastic interface unit, model IU 370. It consists of a top cover and a base. The base has several terminals and a small purple component. The top cover has two screws on top.	<p><b>IU 370</b></p> <p>Interface unit for GD 330/ GD 370/ GD 470</p>
 The image shows a white, cylindrical cable conduit, model CG 100. It has a slightly flared top and bottom edge.	<p><b>CG 100</b></p> <p>Cable Conduit</p>
 The image shows an adhesive kit, model GDK 100. It includes a white spray bottle, a small green bottle, a small red bottle, and a brown cloth.	<p><b>GDK 100</b></p> <p>Adhesive Kit</p>
 The image shows a black, rectangular test unit, model GVT 500. It has a small red light on top and a black button on the front.	<p><b>GVT 500</b></p> <p><b>DISCONTINUED</b> - Replaced by <a href="#">GVT 5000</a></p> <p>Test unit for GD 300/GD 400 Glass Break Detectors.</p>
 The image shows a white, rectangular test unit, model GVT 5000. It has a red button on the front and a black cable connected to it. A small black component is also shown next to it.	<p><b>GVT 5000</b></p> <p>Test Unit for Glass Break and Vibration Detectors</p>

**Related products and accessories****JB 102**

Junction box, 12 screw terminals