

GD 330-S

Glass Break Detector, Glued



Product :

Zone de couverture max.	2 m radius (standard 3 mm glass)
Certifications	EN 50131-2-7-2:2013 Grade 2, VdS class B - G192531, SBSC 10-31, Class 2
Tension de l'alimentation	8-15 VDC
Consommation électrique	5 mA (12 mA in alarm mode)
Sortie alarme	Relay, NC
Cote commutateur	50 VDC / 100 mA
Indicateur d'alarme	LED
Autoprotection	Oui
Durée alarme	Latching
Réinitialisation alarme	Power down
Connexion	Cable / Screw terminals
Matériau du coffret	ABS Plastic
Couleur	Blanc
Indice de protection	IP 67
Dimensions (h x Ø) mm	16 x 35
Dimensions (L x l x h) mm	91 x 31 x 23



Product description:


The GD 330-S has the same features as the GD 330 with relay output and can be directly connected to a control panel via the junction box JB 103-6.

The detector has a coiled cable with modular connector that plugs into the junction box JB 103-6, which allows it to be quickly and easily disconnected from the detector loop when, for example, cleaning windows.

For laminated and tempered glass please use GD 370 or GD 470.

Related products and accessories

	IU 370 Interface unit for GD 330/ GD 370/ GD 470
	CG 100 Cable Conduit
	GDK 100 Adhesive Kit
	GVT 500 DISCONTINUED - Replaced by GVT 5000 Test unit for GD 300/GD 400 Glass Break Detectors.
	GVT 5000 Test Unit for Glass Break and Vibration Detectors

Related products and accessories**JB 103-6**

Junction box for GD 330-S or GD 370-S