

# PSV 1225-18

## Power supply unit, ViP, 12 V 2,5 A

### Product :


Certifications	EN 6100-6:2007 EN 61000-6-3:2007+A1, EN 60950-1:2006 + A11 +A12+A2, CB Test
Tension de l'alimentation	230 VAC
Tension de sortie	13,8 VDC
Intensité de sortie	2,5 A
Emplacement pour batterie (non incluse)	12 V/18 Ah
Autoprotection	Opening and pry off switches
Matériau du coffret	Metal
Couleur	Blanc
Dimensions (L x l x h) mm	300 x 230 x 100




### Product description:

Power supply unit with ViP (Voltage in Parallel) function, 12 VDC 2,5 A.

Power supply unit with ViP function can be connected in parallel to provide more power and redundancy and compensate for voltage drop in the cables. Space is provided for one 12 V/18 Ah accumulator in the metal box which also has opening and pry-off switches. The unit is protected against short-circuiting and overload. Mains failure, low output voltage, battery and fuse failure is indicated via LED and activates separate outputs with relays.

**Related products and accessories****28097**

DC/DC Converter MINI 5-32 V -&gt; 3-30 V

**3097**Power X3, DC / DC Converter  
12-24 VDC -> 5V, 9V, 12V