

28220

RELAY BOX "MINI" 10-30 V DC/AC

Product :

Consommation électrique	@12 VDC - 11.7 mA , @24 VDC - 23.2 mA, @12 VAC - 28.6 mA, @24 VAC - 59.2 mA
Dimensions (L x l x h) mm	58 x 76 x 27
Section câble - borniers	0,14 - 1 mm ²
Tension d'entrée max.	60 V / 2 A
Intensité autoprotection max.	50 mA
Tension min. du relais	10 V

**Product description:****Complete junction box for installation of alarm and access systems.**

Anti-tampering protected junction box, 10-30V DC/AC, 1 relay with 2-pole switching.





LED in series with relay coil.

4 spare terminals available for further connections.

The box is flame-retardant according to UL 94 V-0.

The terminal has screw connection with elevator function.

Related products and accessories

 Two stacks of three cylindrical wall spacers each. Each spacer has a central hole and a smaller hole on the side.	<p>2581.06</p> <p>STACKABLE WALL SPACERS FOR EASY WIRING IN BOX</p>
 A rectangular wall label with a hole on the left side, shown in a perspective view.	<p>3132.01</p> <p>WALL LABEL FOR EASY LABELING</p>
 A silver and black LSA tool with a pointed tip and a handle.	<p>0501.01</p> <p>LSA TOOL FOR KRONE LSA PLUS CONTACTS</p>
 A coiled metal spring.	<p>1901.12</p> <p>SPARE SPRINGS TO FATUM-SERIES</p>