

MC 250-P

Magnetic Contact in Small Format, Recessed mounting, NC



Product :




Montage	Recessed mounting
Circuit du contact	Normalement fermé (NF)
Certifications	EN 50131-2-6 Grade 2, Class IIIA, VdS G 193514 Class B, INCERT B-582-1003, SBSC 9-199, Class 1/2, FG
Cote commutateur	48 VDC / 500 mA / 10 VA
Diamètre de perçage mm	9-10
Aimant (type)	Neodymium (NdFeB)
Distance de fermeture (bois) mm	19
Distance de fermeture en mm (acier)	Depending from the accessories used
Autoprotection	Oui
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	Al-alloy
Température de fonctionnement	-40°C - +70°C
Indice de protection	IP 67
Dimensions du commutateur (L x Ø) mm	23 x 11
Dimensions de l'aimant (L x Ø) mm	15 x 11



Product description:

MC 250 is a universal magnetic contact in small format with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are made of Al-alloy and formed in the shape of a threaded screw, which enables easy installation into wood or plastic. With our extensive range of installation accessories it is easy to install the contact in different kinds of doors and windows.

Related products and accessories

	<p>MC 200-S11</p> <p>Plastic Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>
	<p>MC 200-S21</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>
	<p>MC 200-S31</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p>