


MC 740P BL

DISCONTINUED - Replaced by MC 740-PEMagnetic Contact
Surface mount, NC**Product :**

Montage	Montage en surface
Circuit du contact	Normalement fermé (NF)
Certifications	EN 50131-2-6 Grade 2, Class IIIA, INCERT B-582-0013, VdS G 116504, Class B, SBSC 9-216, Class 1/2, F&P, FG
Cote commutateur	48 VDC / 500 mA / 10 VA
Aimant (type)	Alnico 5
Installation sur bois	Non recommandé
Distance de fermeture (bois) mm	37
Distance de fermeture en mm (acier)	7
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	ABS Plastic
Couleur	Noir
Température de fonctionnement	-40°C - +70°C
Indice de protection	IP 67
Dimensions du commutateur (L x l x h) mm	58 x 14 x 5
Dimensions de l'aimant (L x l x h) mm	58 x 14 x 5

**Product description:**

MC 740 is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing.

The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.