

# HB 120-SW

## Electronic Personal Attack Button with delay function

### Product :

Tension de l'alimentation	8 - 15 VDC
Appel de courant (veille)	7 mA
Appel de courant (alarme)	24 mA
Sortie alarme	2 x Relay, NC
Cote commutateur	50 VDC / 100 mA
Indicateur d'alarme	LED
Autoprotection / Cote	Yes / 12 VDC / 50 mA
Connexion	Screw terminals
Matériau du coffret	ABS Plastic
Couleur	Blanc
Température de fonctionnement	-10 to +55°C
Indice de protection	IP 31
Dimensions (L x l x h) mm	80 x 65 x 30



### Product description:

The HB 120-SW is an advanced electronic personal attack button that can be used for various functions within in an alarm system.

The HB 120-SW has two push buttons that allow for two separate alarm features. Alarm 1 is activated by a dual button function (red LED indicator) and Alarm 2 by a single button function (green LED indicator).

HB 120-SW has a delay function which triggers when the buttons are pressed as follows:

- 1 button pressed independently with 300 millisecond delay**
- 2 buttons pressed together with 2000 millisecond delay**

It has an anti-tamper switch to protect against unauthorised opening. With its flat and compact size it is discreet and easy to install in most types of environments.