

GD 475-S

DISCONTINUED - Replaced by GD 475-SJ

Glass Break Detector for Laminated Glass, Glued, Transistor output



Product :

Zone de couverture max.	2 m radius (Up to 8mm and P8B)
Certifications	VdS EN-ST-000243 (Environmental IIIA, Grade 3), SBSC 17-132 (Class 3), F&P, FG, VdS G 121503 Class B
Tension de l'alimentation	5-15 VDC
Consommation électrique	1,5mA (3 mA in alarm state)
Sortie alarme	Transistor output
Indicateur d'alarme	LED
Autoprotection	Oui
Durée alarme	Latching
Connexion	Câble (connection de cable perpendiculaire)
Matériau du coffret	ABS Plastic
Température de fonctionnement	-40 - +55°C
Indice de protection	IP 67
Dimensions (h x Ø) mm	11 x 26
Grade	3








Product description:

The GD 475-S has the same features as the GD 475 with transistor output and can be directly connected to a control panel via the junction box JB 103-6. The detector has a coiled cable with a modular connector that plugs into the junction box JB 103-6, which allows it to be quickly and easily disconnected from the detector loop when, for example, cleaning windows. The signal from the detector comes on pin 5 & 6 in JB 103-6. Which is connected polarity independent to IU 400 pin 3 & 4.

The cable is made of PUR, which means that it is more elastic and durable than a PVC cable.

Related products and accessories

	<p>CG 100 Cable Conduit</p>
	<p>GDK 100 Adhesive Kit</p>
	<p>GVT 500 DISCONTINUED - Replaced by GVT 5000 Test unit for GD 300/GD 400 Glass Break Detectors.</p>
	<p>GVT 5000 Test Unit for Glass Break and Vibration Detectors</p>
	<p>3041 DISTRIBUTION MODULE 1 > 10 PAIR</p>

Related products and accessories**28041**

Distribution box 1 > 8 pairs