

MC 270-S78 avec résistances intégrées

High Security Magnetic Contact, with built-in resistors



Product :






| | |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Montage | Montage en surface |
| Circuit du contact | Normalement fermé (NF) |
| Certifications | EN 50131-2-6 Grade 3, Class IIIA, VdS G 116033 Class C, SBSC 9-205, Class 3/4, F&P, NBÚ CZ Typ 3, NBÚ SK Typ 3, INCERT B-582-1003 |
| Cote commutateur | 48 VDC / 500 mA / 10 VA |
| Aimant (type) | Alnico 5 |
| Installation sur bois | Uniquement avec accessoires |
| Distance de fermeture (bois) mm | 34 |
| Distance de sabotage (bois) mm | 20 |
| Distance de fermeture en mm (acier) | 25 |
| Distance de sabotage en mm (acier) | 17 |
| Autoprotection | Oui |
| Connexion | Câble (connection de cable perpendiculaire) |
| Matériau du coffret | Aluminium |
| Température de fonctionnement | -40°C - +70°C |
| Indice de protection | IP 67 |
| Dimensions du commutateur (L x l x h) mm | 74 x 30 x 30 |
| Dimensions de l'aimant (L x l x h) mm | 74 x 30 x 30 |
| Grade | 3 |








Product description:

The MC 270-S78 set is intended for exposed environments where a more durable high security contact is needed, such as steel and iron and industrial gates, etc. The set consists of MC 270-C contact with NC contact function installed in MC 200-7 Al housing and an extra strong magnet in MC 200-8 Al housing, which allows for a wide opening gap. MC 270-S78 set contains a 1 m long stainless steel Flexi-tube protection (MC T4). Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.



Related products and accessories

| | |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
|  | <p>MC 200-S3</p> <p>Plastic Housing for MC 240, 246 and 247</p> |
|  | <p>MC 200-S11</p> <p>Plastic Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p> |
|  | <p>MC 200-S12</p> <p>Plastic Flange with Strong Magnet for MC 240, 246, 247, 255</p> |
|  | <p>MC 200-S21</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p> |
|  | <p>MC 200-S22</p> <p>Snap-in Flange with Strong Magnet for MC 240, 246, 247, 255</p> |

Related products and accessories

| | |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
|  | <p>MC 200-S31</p> <p>Plastic Snap-in Flange for MC 240, 246, 247, 250, 255, 270, 272, 275</p> |
|  | <p>MC 200-S32</p> <p>Snap-in Flange with Strong Magnet for MC 240, 246, 247, 255</p> |
|  | <p>MC 200-4</p> <p>Aluminium Housing for MC 240, 246 and 247</p> |
|  | <p>MC 200-5</p> <p>Aluminium Part with Extra Strong Magnet for MC 240, 246 and 247</p> |
|  | <p>MC 200-6</p> <p>Aluminium Housing for Floor Installation for MC 240, 246 and 247</p> |

Related products and accessories

| | |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
|  | <p>MC 200-7</p> <p>Aluminium Housing for MC 240, 246 and 247</p> |
|  | <p>MC 200-8</p> <p>Aluminium Part with Extra Strong Magnet for MC 240, 246 and 247</p> |