

MC 740 BL

Ce produit a été discontinué et remplacé par: MC 740-E

MC 740 is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and
windows against unauthorized opening.

Both the contact and the magnet part are in a water proof (IP 67) plastic housing.

The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.

ADDITIONAL INFORMATION

Longueur de câble (m)	2m, 6m
Certifications	Class 1/2,F&P, class B, Class IIIA, EN 50131-2-6 Grade 2, FG, INCERT B-582-0013, SBSC 9-216, VdS G 116504
Cote commutateur	48 VDC / 500 mA / 10 VA
Température de fonctionnement	-40°C – +70°C
Indice de protection	IP 67
Aimant (type)	Alnico 5
Distance de fermeture (bois) mm	37
Distance de fermeture (acier) mm	7
Dimensions du commutateur (L x l x h) mm	58 x 14 x 5
Dimensions de l'aimant (L x l x h) mm	58 x 14 x 5
Certification de sécurité et schémas d'agrément	EN, F&P, FG, INCERT, SBSC, VdS
Classe de sécurité	2, B
Classe environnementale	IIIA

ORDER INFORMATION

Model	E-NR	Description
MC 740-2BL		
MC 740-6BL		

Alarmtech Sweden AB

Staffansväg 8B | 192 78 Sollentuna | Sweden

alarmtechglobal.com