

MC 740P

E-NR: 6332828

Ce produit a été discontinué et remplacé par: MC 740-PE

MC 740P is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and
windows against unauthorized opening.
Both the contact and the magnet part are in a water proof (IP 67) plastic housing.
The small and thin format makes it especially easy to install in limited
spaces, e.g. on shutters and drawers.

ADDITIONAL INFORMATION

Longueur de câble (m)	2m, 6m, 10m
Certifications	Class 1/2,F&P, class B, Class IIIA, EN 50131-2-6 Grade 2, FG, INCERT B-582-0013, SBSC 9-216, VdS G 116504
Cote commutateur	48 VDC / 500 mA / 10 VA
Température de fonctionnement	-40°C – +70°C
Indice de protection	IP 67
Distance de fermeture (bois) mm	37
Distance de fermeture (acier) mm	X
Dimensions du commutateur (L x l x h) mm	60 x 14 x 5
Dimensions de l'aimant (L x l x h) mm	60 x 14 x 5
Grade	2

ORDER INFORMATION

Model	E-NR	Description
MC 740P	6332828	
MC 740P-6	6332829	
MC 740P-10	6332830	
MC 740PBL		
MC 740PA		

Alarmtech Sweden AB

Staffansväg 8B | 192 78 Sollentuna | Sweden

alarmtechglobal.com