

MC 247

E-NR: 6332714



Magnetic Contact, Recessed mounting, 2xNC



MC 247 is a universal magnetic contact with dual NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are made of Al-alloy and formed in the shape of a threaded screw, which enables easy installation into wood or plastic. With our extensive range of installation accessories it is easy to install the contact either recessed or as a surface mount on metal and other materials. With appropriate accessories, the contact can even be installed on steel doors, safety valves, garage doors, etc. With our extensive range of installation accessories it is easy to install the contact either recessed or as a surface mount on metal and other materials. With appropriate accessories, the contact can even be installed on steel doors, safety valves, garage doors, etc. The contact part is sealed with special epoxy, making it water resistant.

TECHNICAL DETAILS

Cable length	2m, 6m, 10m
Approvals	Class IIIA, CNPP 2124030001C0, EN 50131-2-6 Grade 2, GRADE 2 + RTC, INCERT B-582-1003, SBSC 9-198
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	9-10
Make distance (wood) mm	23
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	37 x 11
Magnet dimensions (L x Ø) mm	37 x 11



Grade	2
Product type	Detectors
Environment	Indoor, Outdoor
Product group	Magnetic contact
Product feature	Flush-mounted
Security certification and approval schemes	EN, FG, INCERT, NF&A2P, SBSC
Security class	2
Environmental class	IIIA
Contact function	2xNC
Mounting on steel	With accessories

ORDER INFORMATION

Model	E-NR	Description
MC 247	6332714	Recessed magnetic contact, 2xNC, 2 m cable
MC 247-6	6332715	Recessed magnetic contact, 2xNC, 6 m cable
MC 247-10	6332716	Recessed magnetic contact, 2xNC, 10 m cable
MC 247-C	6332717	Recessed contact part without magnet, 2xNC, 6 m cable

SCHEMATICS

