

MC 250-P

E-NR: 6332726

Magnetic Contact in Small Format, Recessed mounting, NC

MC 250 is a universal magnetic contact in small format with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are made of Al-alloy and formed in the shape of a threaded screw, which enables easy installation into wood or plastic. With our extensive range of installation accessories it is easy to install the contact in different kinds of doors and windows.

TECHNICAL DETAILS

Built-in resistors	1 x 1K, 1 x 2,2K
Approvals	Class 1/2,FG, Class IIIA, EN 50131-2-6 Grade 2, INCERT B-582-1003, SBSC 9-199, VdS G 193514 Class B
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	9-10
Make distance (wood) mm	19
Make distance (steel) mm	Depending from the accessories used
Contact dimensions (L x Ø) mm	23 x 11
Magnet dimensions (L x Ø) mm	15 x 11
Product type	Detectors
Environment	Indoor, Outdoor
Product group	Magnetic contact
Product feature	Flush-mounted
Security certification and approval schemes	EN, F&P, FG, INCERT, SBSC, VdS

MC 250-P

6 November 2026

Security class	2, B
Environmental class	IIIA
Contact function	NC
Mounting on steel	With accessories

ORDER INFORMATION

Model	E-NR	Description
MC 250-P1K	6332726	Recessed magnetic contact, NC, 1K in parallel, 2 m cable
MC 250-P2,2K	6332727	Recessed magnetic contact, NC, 2,2K in parallel, 2 m cable

SCHEMATICS







