




MC 270-S68

High Security Magnetic Contact for Floor Mounting

E-NR: 6332737

The MC 270-S68 set is intended for exposed environments where a more durable high security contact is needed, such as garage doors, industrial gates of folding or overhead type, etc. The set consists of MC 270-C contact with NC contact function installed in MC 200-6 Al housing and an extra strong magnet in MC 200-8 Al housing, which allows for a wide opening gap. The part to be installed to the floor can bear the weight of a vehicle. MC 270-S68 set contains a 1 m long stainless steel Flexi-tube protection (MC T4). Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone. With appropriate accessories, the contact can even be installed in steel doors, safety valves, garage doors, etc. The contact part is sealed with special epoxy, making it water resistant.

TECHNICAL DETAILS

Approvals

Class 3/4,F&P, Class IIIA, EN 50131-2-6 Grade 3, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-205, VdS G 116030 Class C

Contact rating

48 VDC / 500 mA / 10 VA

Operating temperature

-40°C – +70°C

Housing protection class

IP 67

Make distance (wood) mm

36

Make distance (steel) mm

30

Housing material

Aluminium

Contact dimensions (L x W x H) mm

104 x 40 x 15

Magnet dimensions (L x Ø) mm

74 x 30 x 30

Sabotage distance (wood) mm

17

Grade

3



ORDER INFORMATION

Model	E-NR	Description
MC 270-S68	6332737	High security contact set, NC, 6 m cable

SCHEMATICS

