



MC 346

E-NR: 6332780

Magnetic Contact, Recessed mounting, NC/NO



MC 346 is a universal magnetic contact with change-over (NC/NO) function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation into wood without additional accessories. With our extensive range of installation accessories it is easy to install the contact either recessed or as a surface mount.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class IIIA, CNPP 2124030002B0, EN 50131-2-6 Grade 2, GRADE 2 + RTC, INCERT B-582-1002, SBSC 9-203
Contact rating	48 VDC / 250 mA / 5 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	13
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	36 x 9
Magnet dimensions (L x Ø) mm	26 x 9
Grade	2
Mounting on steel	With accessories
Product type	Detectors
Environment	Indoor, Outdoor
Product group	Magnetic contact
Product feature	Flush-mounted



Security certification and approval schemes	EN, FG, INCERT, NBU, NF&A2P, SBSC
Security class	2
Environmental class	IIIA
Contact function	NC/NO

ORDER INFORMATION

Model	E-NR	Description
MC 346	6332780	Recessed magnetic contact, change-over, 2 m cable
MC 346-5	6332781	Recessed magnetic contact, change-over, 5 m cable
MC 346-10	6332782	Recessed magnetic contact, change-over, 10 m cable
MC 346-C	6332783	Recessed contact part without magnet, change-over, 5 m cable

SCHEMATICS

