

MC 370-S1

E-NR: 6332794

High Security Contact, Recessed Mounting, NC

MC 370-S1 is a high security magnetic contact set with NC function that can be used in both alarm and access control systems for monitoring doors and windows against unauthorized opening. The contact is specially designed for use in banks, museums, art galleries, stores, etc. This set includes the MC 370 and the small plastic adapter set MC 300-S1 for recessed installation with screws in non-magnetic door and window frames. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation into wood without additional accessories. Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class 3/4,FG, Class IIIA, EN 50131-2-6 Grade 3, INCERT B-582-1003, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-207, VdS G 197064 Class C
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	16
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	36 x 9
Magnet dimensions (L x Ø) mm	14 x 9
Sabotage distance (wood) mm	5
Grade	3
Product type	Detectors
Environment	Indoor, Outdoor
Product group	Magnetic contact

ALARMTECH

High quality security solutions

MC 370-S1


6 November 2026

Product feature	Flush-mounted
Security certification and approval schemes	EN, F&P, FG, INCERT, NBU, SBSC, VdS
Security class	3, C
Environmental class	IIIA
Contact function	NC

ORDER INFORMATION

Model	E-NR	Description
MC 370-S1	6332794	Recessed high security contact, NC, 2 m cable
MC 370-S1-5	6332795	Recessed high security contact, NC, 5 m cable
MC 370-S1-10	6332796	Recessed high security contact, NC, 10 m cable

SCHEMATICS



Alarmtech Sweden AB

Staffansväg 8B | 192 78 Sollentuna | Sweden

alarmtechglobal.com