



MC 370-S11

High Security Contact, Recessed Mounting, NC

MC 370-S11 is a high security magnetic contact set with NC function that can be used in both alarm and access control systems for monitoring doors and windows against unauthorized opening. The contact is specially designed for use in banks, museums, art galleries, stores, etc. This set includes MC 370 and the plastic adapter set MC 300-S11 for recessed installation with screws in non-magnetic door and window frames. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation in wood without additional accessories. Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class 3/4, FG, Class IIIA, EN 50131-2-6 Grade 3, INCERT B-582-1003, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-207, VdS G 197064 Class C
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	16
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	36 x 9
Magnet dimensions (L x Ø) mm	14 x 9
Sabotage distance (wood) mm	5
Grade	3



ORDER INFORMATION

Model	E-NR	Description
MC 370-S11	6332854	Recessed high security contact, NC, 2 m cable
MC 370-S11-5	6332855	Recessed high security contact, NC, 5 m cable
MC 370-S11-10	6332856	Recessed high security contact, NC, 10 m cable

SCHEMATICS

