MC 370-S32

E-NR: 6332800

High Security Contact for Steel Doors, NC

MC 370-S32 is a high security magnetic contact set with NC function that can be used in both alarm and access control systems for monitoring doors and windows against unauthorized opening. The contact is specially designed for use in banks, museums, art galleries, stores, etc. This set includes MC 370 and a plastic adapter set MC 300-S32 for recessed mounting with snap-in function in door and window frames. The snap-in function is for material thickness between 1 mm and 1.5 mm. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation without additional accessories. Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class 3/4,FG, Class IIIA, EN 50131-2-6 Grade 3, INCERT B-582-1003, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-207, VdS G 197064 Class C
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	16
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	36 x 9
Magnet dimensions (L x Ø) mm	14 x 9
Sabotage distance (wood) mm	5
Grade	3
Product type	
Environment	Outdoor

ALARMTECH

High quality security solutions

MC 370-S32

7 November 2026

Product group	
Product feature	
Contact function	NC
Mounting on steel	Without accessories

ORDER INFORMATION

Model	E-NR	Description
MC 370-S32	6332800	Recessed high security contact for steel doors, NC, 2 m cable
MC 370-S32-5	6332801	Recessed high security contact for steel doors, NC, 5 m cable
MC 370-S32-10	6332802	Recessed high security contact for steel doors, NC, 10 m cable

SCHEMATICS



Alarmtech Sweden AB

Staffansväg 8B | 192 78 Sollentuna | Sweden

alarmtechglobal.com