

MC 370

E-NR: 6332790

High Security Contact, Recessed Mounting, NC

MC 370 is a high security magnetic contact with NC function that can be used both in alarm and access control systems for monitoring doors and windows against unauthorized opening. The contact is specially designed for use in banks, museums, art galleries, stores, etc. Both the contact and the magnet part are in a water proof (IP 67) plastic housing, which enables easy installation into wood without additional accessories. Contact and magnet are paired. To ensure proper functionality, do not replace the contact or magnet alone.

TECHNICAL DETAILS

Cable length	2m, 5m, 10m
Approvals	Class 3/4,FG, Class IIIA, EN 50131-2-6 Grade 3, INCERT B-582-1003, NBÚ CZ Typ 3, NBÚ SK Typ 3, SBSC 9-207, VdS G 197064 Class C
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Drill diameter mm	8
Make distance (wood) mm	16
Make distance (steel) mm	X
Contact dimensions (L x Ø) mm	36 x 9
Magnet dimensions (L x Ø) mm	14 x 9
Sabotage distance (wood) mm	5
Grade	3
Product type	Detectors

MC 370

6 November 2026

Environment	Indoor, Outdoor
Product group	Magnetic contact
Product feature	Flush-mounted
Application area	
Security certification and approval schemes	EN, F&P, FG, INCERT, NBU, SBSC, VdS
Security class	3, C
Environmental class	IIIA
Contact function	NC
Mounting on steel	With accessories

ORDER INFORMATION

Model	E-NR	Description
MC 370	6332790	Recessed high security contact, NC, 2 m cable
MC 370-5	6332791	Recessed high security contact, NC, 5 m cable
MC 370-10	6332792	Recessed high security contact, NC, 10 m cable
MC 370-BL		Recessed high security contact, NC, 2 m cable, black
MC 370-5BL		Recessed high security contact, NC, 5 m cable, black
MC 370-10BL		Recessed high security contact, NC, 10 m cable, black

SCHEMATICS









