



MC 640-5

E-NR: 6332823

Magnetic contact, Recessed and surface mount, NC



MC 640-5 is a magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and windows against unauthorized opening. Both the contact and the magnet part are in a water proof (IP 67) plastic housing for recessed and surface installation. The accessory MC 600-1 is a flange for installation in hollow profiles or window frames.

TECHNICAL DETAILS

Approvals

Class IIIA VdS G 199523 Class B, EN-ST-000093 Grade 2, F&P, FG, INCERT B-582-1003
SBSC 9-215 Class 2

Contact rating

48 VDC / 500 mA / 10 VA

Housing material, Colour

ABS Plastic

Housing protection class

IP 67

Make distance (wood) mm

24

Make distance (steel) mm

6

Contact dimensions (L x W x H) mm

61 x 9 x 9

Product type

Detectors

Magnet dimensions (L x W x H) mm

61 x 9 x 9

Environment

Indoor, Outdoor

Product group

Magnetic contact

Product feature

Flush-mounted



Security certification and approval schemes	EN, FG, INCERT, SBSC, VdS
Security class	2, B
Environmental class	IIIA
Contact function	NC
Mounting on steel	With accessories

ORDER INFORMATION

Model	E-NR	Description
MC 640-5	6332823	Recessed magnetic contact, NC, 5 m cable
MC 640-5-BL		Recessed magnetic contact, NC, 5 m cable, black

SCHEMATICS

