

MC 740

E-NR: 6332825

This product has been discontinued and replaced with: MC 740-E

MC 740 is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and
windows against unauthorized opening.
Both the contact and the magnet part are in a water proof (IP 67) plastic housing.
The small and thin format makes it especially easy to install in limited spaces, e.g. on shutters and drawers.

TECHNICAL DETAILS

Cable length	2m, 6m, 10m
Approvals	Class 1/2,F&P, class B, Class IIIA, EN 50131-2-6 Grade 2, FG, INCERT B-582-0013, SBSC 9-216, VdS G 116504
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Make distance (wood) mm	37
Make distance (steel) mm	X
Contact dimensions (L x W x H) mm	58 x 14 x 5
Magnet dimensions (L x W x H) mm	58 x 14 x 5
Grade	2

ORDER INFORMATION

Model	E-NR	Description
MC 740	6332825	Magnetic contact, surface mount, NC, 2 m cable
MC 740-6	6332826	Magnetic contact, surface mount, NC, 6 m cable
MC 740-10	6332827	Magnetic contact, surface mount, NC, 10 m cable
MC 740BL		Magnetic contact, black, surface mount, NC, 2 m cable
MC 740A		Magnetic contact, anthracite, surface mount, NC, 2 m cable