

MC 740P

E-NR: 6332828

This product has been discontinued and replaced with: MC 740-PE

MC 740P is a small and thin magnetic contact with NC function that can be used in both alarm and access control systems for monitoring e.g. doors and
windows against unauthorized opening.
Both the contact and the magnet part are in a water proof (IP 67) plastic housing.
The small and thin format makes it especially easy to install in limited
spaces, e.g. on shutters and drawers.

TECHNICAL DETAILS

Cable length	2m, 6m, 10m
Approvals	Class 1/2,F&P, class B, Class IIIA, EN 50131-2-6 Grade 2, FG, INCERT B-582-0013, SBSC 9-216, VdS G 116504
Contact rating	48 VDC / 500 mA / 10 VA
Operating temperature	-40°C – +70°C
Housing protection class	IP 67
Make distance (wood) mm	37
Make distance (steel) mm	X
Contact dimensions (L x W x H) mm	60 x 14 x 5
Magnet dimensions (L x W x H) mm	60 x 14 x 5
Grade	2

ORDER INFORMATION

Model	E-NR	Description
MC 740P	6332828	Magnetic contact, surface mount NC, 2 m cable
MC 740P-6	6332829	Magnetic contact, surface mount NC, 6 m cable
MC 740P-10	6332830	Magnetic contact, surface mount NC, 10 m cable
MC 740PBL		Magnetic contact, surface mount NC, black, 2 m cable
MC 740PA		Magnetic contact, surface mount NC, anthracite, 2 m cable